### **Table of Contents**

Spring Loading the Quartz Bar	2
QBB: EC and CDC side panels (honey-comb aluminum panels)	2
Quartz Bar Box: Button Mounting	3
Elastic Deformation of QBB Buttons, Epoxy Joint Concerns	3
Front Board Signal Routing Discussion	4
HV Connectors and Experiment Services	5
HV Divider Board Final Design Details	6
PMT Pin Selection	6
CAD Design Environment	7
Prism Mounting Components: PEEK elements on Prism sides	7
Calibration Light Source	8
Calibration Light Insertion	8
Quartz Bar Metrology Orientation	9
PMT Module Assembly Test Stand	9
PMT Testing at Nominal Voltage + xx%	10
ECL Flange Detail Needed	10
TOP Cooling	10
Services Allocation Definition	11
Titlo	Errorl Bookmark not defined

01.01	Spring Loading the Quartz Bar	01: Design
need for a mach	rding the loading of the quartz bar and potential ined PEEK block to interface the mirror to the at the forward end of the QBB.	
will be required	extend above and below the mirror (2mm). Testing to determine if there are any optical effects from the the non-mirrored quartz surfaces	
How is the gas so RTV)	eal formed at the forward end of the QBB? (silicone	
	g a counter-bore in the PEEK block—it will help ng located relative to the block.	
	cting mirror vendors and requesting ns regarding contacting the mirror with the PEEK	
OBS: Spring com	npression will be done after the prism is captured at and of the QBB	
	ontacts chosen in order to maintain consistency with this is where there is space available for the cover	
OBS: The glue to	mount the PEEK buttons will be <b>Araldite 2011</b>	

21.01	QBB: EC and CDC side panels (honey-comb aluminum panels)		21: QBB
Discussion rega panels.	rding the full-length thickness of the honeycomb		
accommodate t QBB in order to Current estimat	asing the thickness in the regions available to hicker EC and CDC side honeycomb panels of the increase the mechanical stiffness of the panels.  e is that the Quartz Bar can tolerate only 7mm  re failure; current (modeled?) deviation of the QB is		

### 23.01 Quartz Bar Box: Button Mounting 23: Construction

Discussion about attaching the PEEK buttons to the EC and CDC Quartz Bar box honeycomb panels. Concern expressed about the potential of the surface tension effects of the epoxy used to attach the PEEK buttons to the QBB honeycomb panel surface may allow the PEEK buttons to be pulled away from the flat granite surface of the calibration slab. If this occurs, the PEEK buttons will not be flat but rather follow the contour of EC/CDC QBB panel; optical flatness criteria will be exceeded.

Action 23.01.01: Evaluate the process currently planned to attach the PEEK buttons to the QBB panels and determine if this is going to impact the design of the QBB such that the maximum deflection of the quartz will exceed 0.05mm.

ACTION ITEM		
23.01.01	Due Date:	
Responsibility		
Organization Individual		
KEK		Suzuki
-		-
-		=
-		-
Description		

### 21.02 Elastic Deformation of QBB Buttons, Epoxy Joint Concerns

Action 21.02.01: Provide iTOP collaborators the deformation data for the PEEK QBB buttons under load. The compression deformation data from 0.02mm to 0mm is of most interest.

Action 21.02.02: Engineering Analysis of the epoxy joint of the QBB buttons and the QBB skin. What is the stress on the quartz bar relative to the compliance of the buttons and their location on the panels. We need to understand what the local stress is on the quartz and how this will affect the detector performance. Document the acceptable level in the ICD. Must be assessed for case of different thicknesses of each optic within tolerance of +-0.1 mm (KEK, PNNL)

ACTION ITEM		
21.02.01 Due Date:		
Responsibility		
Organization Individual		
KEK		Suzuki
-		-
-		-
-		-
Description		

21: QBB

	ACTION I	TEM
21.02.02 Due Date:		
Responsibility		
Organization	1	Individual
KEK		Suzuki
PNNL		Fast
-		-
-		-
Description		

07.01	Front Board Signal Routing Discussion	07: PMT/PC Mount
the Front board the Mill-Max lar PC Board surface will allow the PN holes (not throu board fully avail OBS: PMT socke bottom (not closs OBS: PMT pin le of a PC board the OBS: A simple gopins on any PMT	ngths are sufficiently consistent to enable the design at will accommodate the full length of the PMT pin.  o/no-go gauge can be used to ensure no over-length is.  lagoya to add pin length go/no-go test to PMT	

08.01

### **HV Connectors and Experiment Services**

08: HV Supply

Belle II Meeting: <u>We may want/need to bring this topic up to the larger Belle II meeting.</u>

OBS: Direct-soldering the HV cable to the HV PC Board may require that a fixture be fabricated to pre-bend the HV cable in directions and at radii that are consistent with the needs of the QBB electronics box and installation.

ACTION 08.01:Capture the HV Levels in the ICD (data is available in G Visser's presentation)

OBS: The HV Board needs to be redesigned so that the overall board length is shorter and will fit in the QBB electronics box.

OBS: The HV Board may be able to be shortened to 82mm in length (current design is 102mm), but this will require the board be encapsulated (potted)...this will have additional benefit as it provides a safety for the HV signals and provide some mechanical stiffness in critical areas.

OBS: Discussion regarding potting the HV Board to the C-shaped aluminum HV board mounting bracket. This will provide a direct thermal connection to the bracket.

**ACTION 08.02:** 3D print potting dams/walls for the HV board design (PNNL can provide). PNNL and IU will need to resolve layout details of the HV board, potting dam, wire-ways, pogo pins and PEEK retaining plate (on the forward end of the HV board)

OBS: The Pogo-pin being considered for the HV and Front Board design is: Mill-Max P/N: 0926-1-15-20-75-14-11-0

ACTION ITEM		
08.01	Due Date:	
Responsibility		
Organization Individual		
IU		Visser
PNNL		Thompson
-		-
Description		

ACTION ITEM		
08.02 Due Date:		
Responsibility		
Organization Individual		
IU		Visser
PNNL		Fast
-		-
-		-
Description		

08.02	HV Divider Board Final Design Details	08: HV Supply

**HV Divider String Ratio:** 

Current ratio is: 0.3:1:1:1:0.68

Design criteria was: 0.3:1:1:1:0.66

ACTION 08.02.01: Determine the final HV divider ratio and implement the HV divider ratios in the production HV board design. What is optimal for operating at lower gain. Also, if ALD PMTs and non-ALD PMTs are used we may require two separate HV boards in order to operate the two tube types at maximum gain. (Nagoya, Inami, Matsuoka)

OBS: There is an approximate 4 month lead time to procure specific value components for the HV board.

ACTION 08.03.02: HV Board Serial number (this is through i<sup>2</sup>c)—a mini cable that runs to the SCROD board (or other board) We may also want to run i<sup>2</sup>c via pogo pins or a connector from the HV board to one of the other boards in the board stack.

ACTION 08.03.03: Add a Temperature Monitor on the HV board stack (i<sup>2</sup>c)

ACTION ITEM		
08.02.01	. Due Date:	
Responsibility		
Organization Individual		
Nagoya		Inami
Nagoya		Matsouka
-		-
-		-
Description		

DECISION CONCURRENCE 08.02	
Nagoya::Inami Undecided	
U Hawaii: Varner	Undecided
Nagoya:: lijima	Undecided
PNNL:: Asner	Undecided

	ACTION I	TEM	
08.02.02	Due Date:		
1	Responsib	oility	
Organization	Organization Individual		
IU		Visser	
UH		Varner	
-		1	
=		-	
Description			

ACTION ITEM			
08.02.03	Due Date:		
Responsibility			
Organization		Individual	
IU		Visser	
UH		Varner	
-		-	
-		-	
Description		_	

03.01	PMT Pin Selection		03: PMT
Front HV Board:			
OBS: Use Mill-Max #32 socket to connect the PMT to the Front			
board.			
	CP pins connected together or are they isolated from ANSWER: They are all connected)		

## 01.02 CAD Design Environment 01: Design

ACTION 01.02.01: Determine the best interface format for sharing 3D CAD files. [PNNL vaults are using Solid Works 2013]

ACTION 01.02.02: Resolve the Wiki file size limit, need to increase to 50 M Bytes per file (although this should be used sparingly).

**ACTION 01.02.03:** Resolve who will be the official holders of the iTOP drawing archive for the production detector design.

ACTION ITEM			
01.02.01	Due Da	te:	
Responsibility			
Organization Individual			
PNNL		Fast	
UH		Andrew	
-		-	
-		-	
Description			

ACTION ITEM			
01.02.02	Due Da	Due Date:	
Responsibility			
Organization Individual		Individual	
UH		Browder	
-		=	
-		-	
-		=	
Description			

,	ACTION I	TEM
01.02.03	Due Date: 15 Aug 2013	
Responsibility		
Organization Individual		
iTOP Task Force		-
-		-
-		-
-		-
Description		

# 01.03 **Prism Mounting Components: PEEK elements on Prism ends** 01: Design

**OBS:** The PEEK mechanical components on each end of the PRISM will need to be fabricated for each prism used in the production detector to accommodate differences in prism length. This will allow the other QBB parts (e.g. side rails) to all be made the same.

ACTION ITEM				
ID	Due Date:			
Responsibility				
Organization Individual				
-		-		
-		-		
-		-		
-		-		
Description				

iTOP Meeting Notes 3 July 2013 Virginia Tech Meeting

**OBS:** Multi-mode fiber is not going to maintain sufficient timing calibration; single-mode fiber will be needed but single-mode fiber will require a much greater level of power on the light source (pico-second pulsed laser).

**OBS:** PMT Intensity/response Calibration; is a separate issue that is not tied to the calibration light source.

# 15.02 Calibration Light Insertion 15: Calibration ACTION 15.02: A plan/approach and a design for providing ACTION ITEM

calibration light for the iTOP modules is needed. The solution needs to address:

- T0 and delta-T measurements
- PMT illumination
- Fiber-to-Quartz Bar interface
  - o High quality interface
  - Minimal/no TOF photon interference
- Fiber routing (interface to Experiment Services)
- Light Source

<b>ACTION I</b>	TEM		
Due Date:			
Responsibility			
n	Individual		
	Mussa		
	-		
	-		
	-		
	Responsil		

### 09.01 Quartz Bar Metrology Orientation

09: Det. Asst.

**ACTION 09.01.01:** Vendor needs to provide an unequivocal means to establish the reference of the orientation of the metrology measurements made by the vendor. [Note: bar vendors have been contacted to resolve this]

**ACTION 09.01.02:** A table of QA measurements needs to be established, distributed to the iTOP collaborators for the iTOP Assembled Optics.

ACTION ITEM				
09.01.01	Due Date:			
Responsibility				
Organization Individual			Individual	
PNNL		Fast		
-		-		
-		-		
-		-		
Description				

ACTION ITEM			
09.01.02	Due Date:		
F	Responsibility		
Organization		Individual	
UC		Schwartz	
-		-	
-		-	
Description			

03.02 PMT Module Assembly Test Stand

03: PMT

ACTION 03.02: A PMT Module Test Stand needs to be defined, designed and fabricated. This is the final test before the PMT module is attached to the prism. A test plan/approach should also be developed and shared with the iTOP collaborators.

ACTION ITEM			
03.02	Due Da	Due Date:	
Responsibility			
Organization Individual			
KEK		Inami	
UH		Varner	
Nagoya		-	
-		-	
Description			

#### 03.03 03: PMT PMT Testing at Nominal Voltage + xx% OBS: PMTs should be tested to an operating voltage ~100 Volts **ACTION ITEM** greater than the nominal operating voltage. Low gain PMTs should 03.03 Due Date: be tested to "normal" operating voltages. Responsibility Organization Individual KEK Inami ACTION 03.03: Decide if this is warranted and or recommended. Consider contacting Hamamatsu regarding advisability of testing SL-10 PMTs at Nominal Voltage+100V

Description

01.04 ECL Flange Detail Needed 01: Design

ACTION: A detailed drawing and 3D model of the ECL mounting flange is needed. The entire flange needs to be fully detailed to enable a final, detailed design of the iTOP detector model. Specific items include interference identification, cooling tubing and wire routing paths, etc... (Nagoya, Inami) This needs to specifically include the CDC phi adjustment mechanism.

	ACTION	TEM	
ID	Due Da		
	Responsi	bility	
Org	ganization	Individual	
KEK		Inami	
_		-	
-		-	-
-		-	
Description	on		

17.01 **Services Allocation Definition** 17: Expt. Support ACTION 17.01: The Belle II Services Allocation information needs to **ACTION ITEM** be made available to the iTOP collaboration. This information needs 17.01 Due Date: to be shared on a common site (iTOP Twiki) so that all have access to Responsibility the latest information. This information needs to be updated as it Organization Individual KEK Inami changes. iTop Co-Conveners Description

01.06 **Holes in the CDC Support Cylinder** 01: Design ACTION 01.06.01: The CDC detector group needs to be contacted **ACTION ITEM** and the concept of making holes in the CDC support cylinder 01.06.01 Due Date: discussed. (64 10mm holes) (Nagoya, Inami) Responsibility Organization Individual iTOP Co-Conveners ACTION 01.06.02: If the CDC group concurs with the requested modification to the Support Cylinder, a design needs to be completed and reviewed relative to the holes needed by iTOP. This cannot occur until the final version of the board stack is complete. Description **ACTION ITEM** 01.06.02 Due Date: Responsibility Organization Individual **PNNL** Fast UH Andrew Description

#### 01.07 **Final Design Tolerance Analysis** 01: Design ACTION 01.07: An evaluation of tolerances must be completed that **ACTION ITEM** will insure that iTOP detector modules will perform as specified. 01.07 Due Date: This is a very detailed evaluation that will require input from the Responsibility engineering design team and from the scientific measurement team Organization Individual **PNNL** Fast in order to identify all of the critical parameters and to identify all of the mechanical variability in the iTOP detector design. Description

01.08 **iTOP Detector Mechanical Sag Specification** 01: Design **DECISION CONCURRENCE DECISION 01.08:** A decision has been reached that a maximum sag (deviation from the straight condition established during the QBB Nagoya::Inami Concur assembly on the granite slab) of 0.2mm in the radial dimension is U Hawaii: Varner Concur established for the iTOP detector when it is installed in the Belle II Nagoya:: lijima Concur detector. PNNL:: Asner Concur A maximum deviation of 0.5mm is tolerable during assembly and relocation of iTOP detector modules. This imposes a requirement on the strong-back design to insure this dimensional tolerance is not exceeded. 0.5mm deviation represents a safety factor of just 14.

01.07 01: Design **Real-Time & Monitoring QBB Flatness Specification** ACTION 01.07: A method to constantly insure the total deflection of **ACTION ITEM** the QBB remains within specification needs to be included as part of 01.07 Due Date: the QBB Strong Back assembly. This system should provide an Responsibility Individual immediate (real time) alarm if: Organization KEK Suzuki Linear deflection from straight (0mm) exceeds 0.5mm (one Nagoya Kichimi on each long side) Nagoya Kohriki At any time during moving of the assembled quartz modules. Description

TIOI WICCIII	5 Notes 5 July 2015	3 July 2013		Virginia recirivicetiii	
22.01	iTOP Detector Information Database			22: Other	
ACTION 22.01:A database system needs to be designed and implemented to track all of the critical data for the iTOP detector.		22.01	ACTION ITEM 22.01 Due Date:		
tracked. Wh needs to be iTOP collabo	ers need to develop the list of data that should be en this list is complete, a data management system developed and maintained and made available to the ration. Redundancy and data backup needs to be a eration in the design of this system.	Descript	)rganization	Individual ITOP CO-Conveners	
(is there a sir	nilar system in use in the Belle II or other ?)				